



362DN Handheld Rugged Tablet

Slim, Rugged, Multi-functional Wireless Computing

The Wamee 362DN 6" Handheld Rugged Tablet feature Microsoft® Windows®, laden with a powerful Intel® N Series®, the device offers high-performance and energy-efficient operations, while the slim and robust design enhances portability and mobility. With built-in Wi-Fi, BT and GPS connectivity, along with optional features such as 2D barcode scanner, 5 MP front camera and 8 MP back camera to enhance versatility, the 362DN 6" Handheld Rugged Tablet guarantees reliable operation and unbeatable functionality for demanding, mission-critical environments.



Features

- 6" capacitive touch screen, digital pen support
- Intel® Core® i3-N300
- Microsoft® Windows® 10/11 IoT Enterprise
- Hot-swappable battery pack
- IP65-rated for water and dust resistance
- MIL-STD-810G for shock and vibration protection
- Discrete TPM 2.0

Major Options

- Barcode scanner
- NFC or UHF RFID reader
- 5 MP front camera/8 MP back camera
- GPS module

Specifications



SPECIFICATIONS		362DN
System		
CPU	Intel® Core® i3-N300 8-Core (up to 3.80 GHz); N200 4-Core (up to 3.7GHz)	
RAM	16GB	
Storage	256GB ~ 1TB Flash (Removable)	
Operating System	Microsoft® Windows® 10/11 IoT Enterprise	
Compliance	NIST Compliant BIOS Available: TPM 2.0	
Display	6" LED-Backlit (350 nits) touchscreen	
Display Resolution	1440 x 720	
Control Switch and Buttons	1 x Power Button, 2 x Programmable Buttons	
Speaker	Built-in Speaker	
Microphone	Built-in Microphone	
Network Interface		
WLAN	Wi-Fi 802.11ac, 2.4/5 GHz Dual Band	
BT	Yes	
GPS	Yes	
I/O Ports		
USB Port	USB Type-C x 1 (data transmitting and charging; data transmitting only available in one insertion direction)	
Micro SIM Card Slot	N/A	
Smart Reader/CAC Reader	Full Slot (Reads ISO 7816 T=0, T=1); 1.8/3/5V Smart Card	
Micro SD Slot	N/A	
Mechanical & Environmental		
AC/DC Adapter	Input: 100 ~ 240V AC; Output: 20V DC, 3.25A	
Battery Pack	Hot-Swappable Battery (2700mAh)	
Enclosure	ABS + PC Plastic	
Dimensions (HxWxD)	192 x 95 x 31 mm	
Weight	485 g	
Regulatory	CE, FCC Class B, RoHS, UL	
Temperature	Operation: 0°C ~ 50°C (32°F ~ 122°F); Storage: -20°C ~ 60°C (-4°F ~ 140°F)	
Humidity	0% ~ 90% Non-Condensing	
Major Option		
Camera	5 MP Front USB Camera & 8 MP Back Camera	
Barcode Scanner	2D Barcode Scanner (Reads 1D & 2D); Long Range 2D Barcode Scanner (up to 60ft)	
NFC/RFID Reader	HF 13.56 MHz, ISO 15693, 14443A(B) & 18000-3 Mode 1	
UHF RFID Reader	865 ~ 928MHz, EPCglobal Class 1 Gen 2/ISO 18000-6C; 16 ft (4.87m) Reading Distance with the Built-In ThingMagic Micro Module & Embedded Antenna; 30 ft (9.1m) Reading Distance with Trigger Grip	

* Specifications subject to change without notice

DIGITAL PEN



BATTERY PACK



CHARGING CRADLE



4 BAY GANG CHARGER



PISTOL GRIP FOR BARCODE SCANNER



PISTOL GRIP WITH UHF RFID

