



## Wamee 361ND Rugged Tablet

### Slim, Rugged, Multi-functional Wireless Computing

The Wamee 361ND Handheld Rugged Tablet features a 6" LED 850 nits touchscreen and a Qualcomm® 8-core processor in a slim, lightweight, and durable package. The 361ND is engineered for durability and reliability to ensure dependable performance even in harsh environments, offering an optional Fischer MiniMax connector. With IP65 and MIL-STD-810H certifications, the 361ND ensures reliable performance in demanding, mission-critical environments.



### Features

- 6" LED 850 nits touchscreen, capacitive stylus support
- Qualcomm® 8-core processor
- Android 13 operating system
- Hot-swappable battery pack
- IP65-rated for water and dust resistance
- MIL-STD-810H for shock and vibration protection
- Wide operating temperature range

### Major Options

- Waterproof 24-pin Fischer MiniMax connector

# Specifications



## SPECIFICATIONS **361ND**

### System

<b>CPU</b>	Qualcomm® 8-core (1.9 GHz to 2.7 GHz)
<b>Storage and RAM</b>	256GB Flash with 12GB RAM
<b>Operating System</b>	Android 13
<b>Security Features</b>	ARM® TrustZone® (built-in)
<b>Display</b>	6" LED 850 nits touchscreen
<b>Display Resolution</b>	1440 x 720
<b>Switch and Button</b>	1 x power button; 1 x day/night vision switch; 2 x programmable buttons
<b>Speaker</b>	Built-in speaker

### Network Interface

<b>WLAN</b>	Wi-Fi 802.11ax, 2.4/5/6 GHz three band
<b>BT</b>	5.2

### I/O Ports

<b>USB Port</b>	1 x latest USB/charging
<b>24-pin Fischer Minimax Connector (optional)</b>	Ethernet, USB-3.2 5G/USB2.0, and power 5-6A (in) and power 2A (out)/ground/URAT

### Mechanical & Environmental

<b>AC/DC Adapter</b>	Input: 100 to 240V AC; Output: 15V DC, 3A
<b>Battery Pack</b>	23W swappable battery (7.6V, 3100mAh)
<b>Enclosure</b>	ABS + PC plastic and magnesium-aluminum alloy
<b>Dimensions (HxWxD)</b>	94.8 x 192.8 x 29.36 mm
<b>Weight</b>	0.45 kg
<b>Durability</b>	IP65 and MIL-STD-810H
<b>Regulatory</b>	CE, FCC Class B, and RoHS compliant
<b>Temperature</b>	Operation: -10°C to 50°C (14°F to 122°F); Storage: -55°C to 70°C (-67°F to 158°F)
<b>Humidity</b>	0% to 90% non-condensing

\* Specifications subject to change without notice

## Accessories

### CAPACITIVE STYLUS



### 6-BAY BATTERY GANG CHARGER



### BATTERY PACK

