Wamee 381WF Tactical Tablet

Slim, Rugged, Multi-functional Wireless Computing

The 381WF Tactical Tablet features an 8" LED 850 nits touchscreen and a high-performance, energy efficient Intel® Core™ 3 N355 processor within a slim, lightweight, durable package. With built-in Wi-Fi, BT connectivity, optional 2D barcode scanner, RFID reader, and front/back cameras options, the robust tablet offers seamless information capture and transmission for improved workflow. With IP65 and MIL-STD-810H certification, the 381WF Tactical Tablet provides reliable operation in harsh, mission-critical environments.

Features

- 8" LED 850 nits touchscreen, capacitive stylus support
- Intel® Core™ 3 N355 processor
- Microsoft® Windows® 11 operating system
- IP65-rated for water and dust resistance
- MIL-STD-810H for shock and vibration protection
- Hot-swappable battery pack

Major Options

- 5 MP front camera and 8 MP back camera
- 2D barcode scanner (reads 1D and 2D)
- RFID reader
- Waterproof 24-pin Fischer MiniMax connector

Specifications

SPECIFICATIONS	381WF	
System		
CPU	Intel® Core™ 3 N355, Octa-core (up to 3.9 GHz)	
Storage and RAM	512GB or 1TB removable SSD with 16GB RAM	
Operating System	Microsoft® Windows® 11 IoT Enterprise	
NIST Compliance	NIST compliant BIOS available	
Display	8" LED 850 nits touchscreen	
Display Resolution	800 x 1280	
Control Switch and Buttons	1 x power button, 1 x programable button	
Microphone	Built-in microphone	
Speaker	Built-in speaker	
Network Interface		
WLAN	Wi-Fi 802.11be, 2.4/5/6 GHz three band	
BT	5.4	
I/O Ports		
USB Port	1 x USB-A; 1 x latest USB/charging	Standard
Ethernet	Ethernet 10/ 100/ 1000MB Base-T LAN	
DC-in	1	
MicroSD Slot	1 x microSD card slot	
24-pin Fischer Minimax Connector (optional)	Ethernet, USB-3.2 5G/USB2.0, and power 5-6A (in) and power 2A (out)/ground/URAT	Optional
Mechanical & Environmental		
AC/DC Adapter	Input: 100 to 240V AC; Output: 19V DC, 3.25A	
Battery Pack	25W Hot-swappable battery (7.6V, 3350mAh)	
Enclosure	ABS + PC plastic and magnesium-aluminum alloy	
Dimensions (HxWxD)	152.56 x 216.94 x 20.0 mm	
Weight	780g (with battery)	
Durability	IP65 and MIL-STD-810H	
Regulatory	FCC Class B, CE, RoHS compliant	
Temperature	Operation: -20°C to 60°C (-4°F to 140°F); Storage: -20°C to 60°C (-4°F to 140°F)	
Humidity	0% to 90% non-condensing	
Major Option		
Barcode Scanner	2D Barcode Scanner (Reads 1D and 2D)	
Camera	5 MP front camera and 8 MP back camera	
RFID Reader	Dual frequency (reads 125 KHz and 13.56 MHz credentials)	

* Specifications subject to change without notice

Accessories

CAPACITIVE STYLUS

4-BAY BATTERY GANG CHARGER

BATTERY PACK